

BACK-TV SATS HD 7" TRÅDLÖS MED KAMERA

Artikelnr. 27-7001, 27-7002

A1. Model No.:

SV-HDW700127SC

SV-HDW143671CAI

A2. Product Name:

7" 2.4GHz Digital Wireless Dual-View System

B1. Product Keywords:



Monitor:	Camera:
<ul style="list-style-type: none"> - TFT LCD monitor with wide angle view and high resolution display - Support 4 HD channels wireless camera input - Recording function (128GB TF card) - Auto pairing: Auto pairing happens when camera is activated - 10V-32V wide operation voltage - Automatic backlighting and light control - Reverse gear activated screen - Picture image adjustable for Horizontal/Vertical/ Mirror/Normal viewing 	<ul style="list-style-type: none"> - Water resistant housing - Nightvision distance: approx. 15 m (4 infrared lights) - 10V-32V wide power supply input available - Smart IR function available - Anti-vibration: ISO 16750-3 (Max. 17.3G)

B2. Key Specifications:

Monitor:		Camera:	
LCD size:	7"	Image Device:	1/4" CMOS HM1246
Resolution:	1024 x 3 (RGB) x 600	TV System:	PAL/NTSC
Contrast:	800:1	Effective Pixels:	1280 (H) x 720 (V)
Brightness:	500 cd/m ²	Pixel size:	3.0um x 3.0um
Viewing Angle:	U:70/D:75, R/L:75	Scanning System:	Progressive Scanning
Aspect Ratio:	16:9	Sync. System:	Internal
Channel:	4 channels	Minimum Illumination:	0.1 Lux (day), 0 Lux (with IR)
Operating Frequency:	2412 - 2467 MHz	Microphone:	Yes
Transmitting Distance:	300 m	Video Output:	8 bits YUV
Receiving Sensitivity:	-85 dBm	AGC:	Auto
Decompression Format:	H.264	S/N Ratio:	S/N(a-weighted) 101.6dB
Modulation:	DSSS	White Balance:	Auto
Micro-SD /TF Card:	Max. 128G	BLC:	Auto
Time Delay:	200 ms	Operation Frequency:	2412 MHz ~ 2467 MHz
System Format:	PAL/NTSC	Receiving Sensitivity:	-85 dBm
Power Consumption:	Max. 8W	Video Code:	H.264
Loudspeaker:	1.5W/8Ω	Transmitting distance:	300M (barrier free)
Operating Temperature:	-20~+70°C, RH 90%	Spread Spectrum:	DSSS
Storage Temperature:	-30~+80°C, RH 90%	Transmit output power:	18 dBm
		Delay:	200 ms
		RF Bit Rate:	12 Mbps
		Operating Temperature:	-20°C~70°C, RH 90% MAX.
		Storage Temperature:	-30°C~80°C, RH 90% MAX.

C1. Accessories:

Monitor: Power supply cable, 2- 5dB antennas, Manual, IR remote control, Sun shield, Center mount bracket, U-support bracke, L-shape offset ring wrench

Camera: Manual, Hex wrench, DC power cable, 3dB antenna

D1. Packing: Weight Of Unit Product: 3,5 kg. Weight Of Export Carton: 1 kg.

Dimension Of Giftbox: 34.2 x 19.3 x 8.6 cm. Dimension Of Export Carton: 45 x 35.5 x 41 cm.