


KAMERA FÄRG MED VISIR

Artikelnr. 27-CM11B

Auto-Shutter Camera AE-CM11B	
Main Feature:	
<ul style="list-style-type: none"> · Motorized Shutter. · Stainless brackets & aluminum alloy housing. <p>For electronic and software design:</p> <ul style="list-style-type: none"> · The shuttering flip can open automatically when the reversing gear is engaged · If it's blocked, in the definite time (5second), the camera will stop shuttering automatically to protect the inner component and circuit board <p>Excellence features , Unique Application:</p> <ul style="list-style-type: none"> · Can be used under heavy duty,(air turbulence, dirty water, rainy days, winter time, dirty roads & when powerful pressure water cleaning machine) <p>For mechanical design:</p> <ul style="list-style-type: none"> · The user can open or close the cover manually according to working purpose · Auto-open the cover when shift the rear gear · The spindle of cover is separated with the inner wheel. There is a spring slice between them as a buffer. Then even if outside cover is blocked, it won't affect the inner wheel and circuit board · 18pcs IR LEDs for night vision (10-12 m) 	
Technical Data:	
Image type:	Color Sharp CCD
Color System:	PAL/NTSC
Resolution (pixels) :	PAL: 752(H)x 582(V)
Image Size:	1/4 inch
Lens: Focal Length:	3.0 mm, F2.0
Lens angle:	126°(diagonal)
Horizontal Resolution:	600 TV Lines
Synchronization:	Internal
Power Supply:	DC12V±10%
Power Consumption:	≤2.5W
Signal to Noise Ratio:	>46dB
Waterproof & dust resistance grade:	IP68
Operating Temperature Range:	-30 °C to +70 °C
Storage Temperature Range:	-40 °C to +80 °C
Dimension:	105(L) x 65(W) x 93 (H) mm
Weight Approx:	588 g