

LCD FÄRG 7" QUAD IP65 TRIGG QUAD

Artikelnr. 27-TM70MT

A1. Model No.:

AE-TM70M

A2. Product Name:

7" TFT LCD QUAD SPLIT SCREEN MONITOR

B1. Main Feature:

- The color TFT LCD monitor is designed for heavy duty field.
- With built-in quad control box function.
- Support four camera inputs.
- With built-in speaker.
- Die casting rear housing and heavy duty harness
- Automatically adjust the display mode according to the qty of camera inputs
- Single View/Split view/Quad view selectable , triple view available when only 3 camera inputs
- Automatically switches to the camera when triggered. Trigger priority: CAM 1>CAM 2>CAM 3>CAM 4
- 7 languages OSD display
- Mirror/Normal image can be set in the MENU for each camera separately.
- User can choose the day/night mode by pressing the "D/N" button.
- With high-low voltage and short-circuit protection.

B2. Technical data:

- 7 inch TFT LCD monitor, 16:9
- Resolution: 800 x (RGB) x 480 (pixels)
- Wide view angle (CR>10) : (up/ down): 40/60; (left/right): 60/60
- Brightness (cd/m2): 450
- Contrast ratio: 300
- Color system: PAL/NTSC (AUTO)
- With soon respond (ms) (at 25°C):20
- Waterproof: IP65
- Power requirement: 12/24V DC
- Voltage Range: 10~30V
- Power consumption: ≤5W
- Operating temperature: -30 °C to +75 °C
- Storage temperature: -40 °C to +80 °C
- Dimension: 200(L) x 138.5(W) x 76(D) mm
- Weight approx: 800±10g (without bracket)

