

RINGKABELSKO RÖD 6.4MM 0.5-1.5MM 100ST

Art.nr: 16-RV1-6

Ringkabelsko röd isolerad. Hål 6,4 mm, M6. För kabel area 0,5-1,5 mm². Förpackning 100 st.

Teknisk information

Mått (LxHxB)	6,4 mm
Kabelarea	Röd 0,5-1,5 mm²
Stift/Hylsa/Tätning/Hus /Skarv	Ringkabelsko
Antal i B-pack	100 st
Vikt (kg)	0.200000




PVC DIN RING TERMINAL - EASY ENTRY

PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Terminal: Copper, tin plated
Insulation: Vinyl (PVC)
Operating temperature: -10-75 °C
Max. electrical current: 600V
Max. electrical rating: red 19A
blue 27A
yellow 48A



DIMENSIONS

Wire range	Part nr.	Od2	W	F	L	B	OD	Od1	T	UL
22-16 AWG 0.5-1.5 mm²	REFD 1.25-32IN	3.2	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	REFD 1.25-34IN	3.7	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	REFD 1.25-40IN	4.3	6.0	17.0	21.0	10.0	4.3	1.7	0.75	
	REFD 1.25-50IN	5.3	10.0	18.0	23.0	10.0	4.3	1.7	0.75	
	REFD 1.25-60IN	6.5	11.0	20.0	25.5	10.0	4.3	1.7	0.75	
	REFD 1.25-80IN	8.4	14.0	22.0	29.0	10.0	4.3	1.7	0.75	
16-14 AWG 1.5-2.5 mm²	REFD 1.25-100IN	10.5	18.0	24.0	33.0	10.0	4.3	1.7	0.75	
	REFD 2.5-32IN	3.2	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	REFD 2.5-38IN	3.7	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	REFD 2.40IN	4.3	6.0	17.0	21.0	10.0	5.0	2.3	0.8	
	REFD 2.50IN	5.3	10.0	18.0	23.0	10.0	5.0	2.3	0.8	
	REFD 2.60IN	6.5	11.0	21.0	26.5	10.0	5.0	2.3	0.8	
12-10 AWG 4-6 mm²	REFD 2.80IN	8.4	14.0	22.0	29.0	10.0	5.0	2.3	0.8	
	REFD 2.100IN	10.5	18.0	24.0	33.0	10.0	5.0	2.3	0.8	
	REFD 2.112IN	13.0	18.0	25.0	34.0	10.0	5.0	2.3	0.8	
	REFD 5.5-40IN	4.3	6.0	21.0	25.0	13.0	6.7	3.4	1.0	
	REFD 5.5-50IN	5.3	10.0	22.0	27.0	13.0	6.7	3.4	1.0	
	REFD 5.5-60IN	6.5	11.0	22.5	28.0	13.0	6.7	3.4	1.0	
	REFD 5.5-80IN	8.4	14.0	26.0	31.0	13.0	6.7	3.4	1.0	
	REFD 5.5-100IN	10.5	18.0	28.0	33.0	13.0	6.7	3.4	1.0	
	REFD 5.5-120IN	13.0	18.0	28.0	33.0	13.0	6.7	3.4	1.0	