

RINGKABELSKO BLÅ 8.4MM 1.5-2.5MM 100ST

Art.nr: 16-RV2-8

Ringkabelsko blå isolerad. Hål 8,4 mm, M8. För kabel area 1,5-2,5 mm². Förpackning 100 st.

Teknisk information

Mått (LxHxB)	8,4 mm
Kabelarea	Blå 1,5-2,5 mm ²
Stift/Hylsa/Tätning/Hus /Skarv	Ringkabelsko
Antal i B-pack	100 st
Vikt (kg)	0.200000



PVC DIN RING TERMINAL - EASY ENTRY


PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Terminal:
Insulation:
Operating temperature:
Max. electrical current:
Max. electrical rating:

Copper, tin plated
Vinyl (PVC)
-10~75 °C
600V
red 19A
blue 27A
yellow 48A



DIMENSIONS

Wire range	Part nr.	Od2	W	F	L	B	OD	Od1	T	UL
22-16 AWG 0.5-1.5 mm ²	REFD 1.25-32IN	3.2	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	REFD 1.25-34SDIN	3.7	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	REFD 1.25-40IN	4.3	6.0	17.0	21.0	10.0	4.3	1.7	0.75	
	REFD 1.25-50IN	5.3	10.0	18.0	23.0	10.0	4.3	1.7	0.75	
	REFD 1.25-60IN	6.5	11.0	20.0	25.5	10.0	4.3	1.7	0.75	
16-14 AWG 1.5-2.5 mm ²	REFD 1.25-80IN	8.4	14.0	22.0	29.0	10.0	4.3	1.7	0.75	
	REFD 1.25-100IN	10.5	18.0	24.0	33.0	10.0	4.3	1.7	0.75	
	REFD 2-51 SDIN	3.2	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	REFD 2-58SDIN	3.7	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	REFD 2-60IN	4.3	6.0	17.0	21.0	10.0	5.0	2.3	0.8	
12-10 AWG 4-6 mm ²	REFD 2-80IN	5.3	10.0	18.0	23.0	10.0	5.0	2.3	0.8	
	REFD 2-80IN	6.5	11.0	21.0	26.5	10.0	5.0	2.3	0.8	
	REFD 2-100IN	8.4	14.0	22.0	29.0	10.0	5.0	2.3	0.8	
	REFD 2-100IN	10.5	18.0	24.0	33.0	10.0	5.0	2.3	0.8	
	REFD 2-112IN	13.0	18.0	25.0	34.0	10.0	5.0	2.3	0.8	
4-6 mm ²	REFD 5.5-40IN	4.3	6.0	21.0	25.0	13.0	6.7	3.4	1.0	
	REFD 5.5-50IN	5.3	10.0	22.0	27.0	13.0	6.7	3.4	1.0	
	REFD 5.5-60IN	6.5	11.0	22.5	28.0	13.0	6.7	3.4	1.0	
	REFD 5.5-80IN	8.4	14.0	26.0	31.0	13.0	6.7	3.4	1.0	
	REFD 5.5-100IN	10.5	18.0	28.0	33.0	13.0	6.7	3.4	1.0	
	REFD 5.5-120IN	13.0	18.0	28.0	37.0	13.0	6.7	3.4	1.0	