

RINGKABELSKO GUL 10.5MM 4-6MM 100ST

Art.nr: 16-RV5-10

Ringkabelsko gul isolerad. Hål 10,5mm, M10. För kabel area 4-6mm². Förpackning 100st.

Teknisk information

Mått (LxHxB)	10,5 mm
Kabelarea	Gul 4-6 mm ²
Stift/Hylsa/Tätning/Hus /Skarv	Ringkabelsko
Antal i B-pack	100 st
Vikt (kg)	0.350000




PVC DIN RING TERMINAL - EASY ENTRY

PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Terminal: Copper, tin plated
Insulation: Vinyl (PVC)
Operating temperature: -10-75 °C
Max. electrical current: 600V
Max. electrical rating: red 19A
blue 27A
yellow 48A



DIMENSIONS

Wire range	Part nr.	Od2	W	F	L	B	OD	Od1	T	UL
22-16 AWG 0.5-1.5 mm ²	REPO 1.25-32IN	3.2	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	REPO 1.25-34IN	3.7	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	REPO 1.25-40IN	4.3	6.0	17.0	21.0	10.0	4.3	1.7	0.75	
	REPO 1.25-50IN	5.3	10.0	18.0	23.0	10.0	4.3	1.7	0.75	
	REPO 1.25-60IN	6.5	11.0	20.0	25.5	10.0	4.3	1.7	0.75	
16-14 AWG 1.5-2.5 mm ²	REPO 1.25-80IN	8.4	14.0	22.0	29.0	10.0	4.3	1.7	0.75	
	REPO 1.25-100IN	10.5	18.0	24.0	33.0	10.0	4.3	1.7	0.75	
	REPO 2-50IN	3.2	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	REPO 2-58IN	3.7	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	REPO 2-60IN	4.3	6.0	17.0	21.0	10.0	5.0	2.3	0.8	
12-10 AWG 4-6 mm ²	REPO 2-80IN	5.3	10.0	18.0	23.0	10.0	5.0	2.3	0.8	
	REPO 2-82IN	6.5	11.0	21.0	26.5	10.0	5.0	2.3	0.8	
	REPO 2-84IN	8.4	14.0	22.0	29.0	10.0	5.0	2.3	0.8	
	REPO 2-100IN	10.5	18.0	24.0	33.0	10.0	5.0	2.3	0.8	
	REPO 2-112IN	13.0	18.0	25.0	34.0	10.0	5.0	2.3	0.8	
12-10 AWG 4-6 mm ²	REPO 5.5-40IN	4.3	6.0	21.0	25.0	13.0	6.7	3.4	1.0	
	REPO 5.5-50IN	5.3	10.0	22.0	27.0	13.0	6.7	3.4	1.0	
	REPO 5.5-60IN	6.5	11.0	22.5	28.0	13.0	6.7	3.4	1.0	
	REPO 5.5-80IN	8.4	14.0	24.0	31.0	13.0	6.7	3.4	1.0	
	REPO 5.5-100IN	10.5	18.0	26.0	33.0	13.0	6.7	3.4	1.0	
	REPO 5.5-120IN	13.0	18.0	28.0	37.0	13.0	6.7	3.4	1.0	