

RINGKABELSKO GUL 8.4MM 4-6MM² 100ST

Art.nr: 16-RV5-8

Ringkabelsko gul isolerad. Hål 8,4mm, M8. För kabel area 4-6mm². Förpackning 100st.

Teknisk information

Mått (LxHxB)	8,4 mm
Kabelarea	Gul 4-6 mm ²
Stift/Hylsa/Tätning/Hus /Skarv	Ringkabelsko
Antal i B-pack	100 st
Vikt (kg)	0.300000




PVC DIN RING TERMINAL - EASY ENTRY

PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Terminal: Copper, tin plated
Insulation: Vinyl (PVC)
Operating temperature: -10-75 °C
Max. electrical current: 600V
Max. electrical rating: red 19A
blue 27A
yellow 48A



DIMENSIONS

Wire range	Part nr.	Qd2	W	F	L	B	OD	Qd1	T	UL
22-16 AWG 0.5-1.5 mm ²	REFD 1.25-32IN	3.2	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	REFD 1.25-34IN	3.7	6.0	16.0	19.0	10.0	4.3	1.7	0.75	
	REFD 1.25-40IN	4.3	6.0	17.0	21.0	10.0	4.3	1.7	0.75	
	REFD 1.25-50IN	5.3	10.0	18.0	23.0	10.0	4.3	1.7	0.75	
	REFD 1.25-60IN	6.5	11.0	20.0	25.5	10.0	4.3	1.7	0.75	
16-14 AWG 1.5-2.5 mm ²	REFD 1.25-80IN	8.4	14.0	22.0	29.0	10.0	4.3	1.7	0.75	
	REFD 1.25-100IN	10.5	18.0	24.0	33.0	10.0	4.3	1.7	0.75	
	REFD 2.5-32IN	3.2	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	REFD 2.5-34IN	3.7	6.0	16.0	19.0	10.0	5.0	2.3	0.8	
	REFD 2.5-40IN	4.3	6.0	17.0	21.0	10.0	5.0	2.3	0.8	
12-10 AWG 4-6 mm ²	REFD 2.5-50IN	5.3	10.0	18.0	23.0	10.0	5.0	2.3	0.8	
	REFD 2.5-60IN	6.5	11.0	20.0	25.5	10.0	5.0	2.3	0.8	
	REFD 2.5-80IN	8.4	14.0	22.0	29.0	10.0	5.0	2.3	0.8	
	REFD 2.5-100IN	10.5	18.0	24.0	33.0	10.0	5.0	2.3	0.8	
	REFD 2.5-120IN	13.0	18.0	25.0	34.0	10.0	5.0	2.3	0.8	
6-4 mm ²	REFD 5.5-40IN	4.3	6.0	21.0	25.0	13.0	6.7	3.4	1.0	
	REFD 5.5-50IN	5.3	10.0	22.0	27.0	13.0	6.7	3.4	1.0	
	REFD 5.5-60IN	6.5	11.0	22.5	28.0	13.0	6.7	3.4	1.0	
	REFD 5.5-80IN	8.4	14.0	24.0	31.0	13.0	6.7	3.4	1.0	
	REFD 5.5-100IN	10.5	18.0	26.0	33.0	13.0	6.7	3.4	1.0	
	REFD 5.5-120IN	13.0	18.0	28.0	37.0	13.0	6.7	3.4	1.0	