

## RINGKABELSKO BLÅ 5.3MM 1.5-2.5MM 100ST

Art.nr: 16-RVS2-5

Ringkabelsko blå isolerad. Hål 5,3 mm, M5. För kabel area 1,5-2,5 mm<sup>2</sup>. Förpackning 100 st.

### Teknisk information

|                                |                             |
|--------------------------------|-----------------------------|
| Mått (LxHxB)                   | 5,3 mm                      |
| Kabelarea                      | Blå 1,5-2,5 mm <sup>2</sup> |
| Stift/Hylsa/Tätning/Hus /Skarv | Ringkabelsko                |
| Antal i B-pack                 | 100 st                      |
| Vikt (kg)                      | 0.150000                    |




PVC DIN RING TERMINAL - EASY ENTRY

PHOTO / TECHNICAL DRAWING



TECHNICAL SPECIFICATIONS

Terminal: Copper, tin plated  
Insulation: Vinyl (PVC)  
Operating temperature: -10-75 °C  
Max. electrical current: 600V  
Max. electrical rating: red 19A  
blue 27A  
yellow 48A



DIMENSIONS

| Wire range                           | Part nr.         | Qd2  | W    | F    | L    | B    | QD  | Qd1 | T    | UL |
|--------------------------------------|------------------|------|------|------|------|------|-----|-----|------|----|
| 22-16 AWG<br>0.5-1.5 mm <sup>2</sup> | REFPO 1.25-32IN  | 3.2  | 6.0  | 16.0 | 19.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REFPO 1.25-34IN  | 3.7  | 6.0  | 16.0 | 19.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REFPO 1.25-40IN  | 4.3  | 6.0  | 17.0 | 21.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REFPO 1.25-50IN  | 5.3  | 10.0 | 18.0 | 23.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REFPO 1.25-60IN  | 6.5  | 11.0 | 20.0 | 25.5 | 10.0 | 4.3 | 1.7 | 0.75 |    |
| 16-14 AWG<br>1.5-2.5 mm <sup>2</sup> | REFPO 1.25-80IN  | 8.4  | 14.0 | 22.0 | 29.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REFPO 1.25-100IN | 10.5 | 18.0 | 24.0 | 33.0 | 10.0 | 4.3 | 1.7 | 0.75 |    |
|                                      | REFPO 2.5-120IN  | 12.5 | 6.0  | 18.0 | 19.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REFPO 2.5-130IN  | 13.7 | 6.0  | 18.0 | 19.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REFPO 2.40IN     | 4.3  | 6.0  | 17.0 | 21.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
| 12-10 AWG<br>4-6 mm <sup>2</sup>     | REFPO 2.50IN     | 5.3  | 10.0 | 18.0 | 23.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REFPO 2.60IN     | 6.5  | 11.0 | 21.0 | 26.5 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REFPO 2.80IN     | 8.4  | 14.0 | 22.0 | 29.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REFPO 2.100IN    | 10.5 | 18.0 | 24.0 | 33.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
|                                      | REFPO 2.112IN    | 13.0 | 18.0 | 25.0 | 34.0 | 10.0 | 5.0 | 2.3 | 0.8  |    |
| 12-10 AWG<br>4-6 mm <sup>2</sup>     | REFPO 5.5-40IN   | 4.3  | 6.0  | 21.0 | 25.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
|                                      | REFPO 5.5-50IN   | 5.3  | 10.0 | 22.0 | 27.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
|                                      | REFPO 5.5-60IN   | 6.5  | 11.0 | 22.5 | 28.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
|                                      | REFPO 5.5-80IN   | 8.4  | 14.0 | 26.0 | 33.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
|                                      | REFPO 5.5-100IN  | 10.5 | 18.0 | 28.0 | 37.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |
| 12-10 AWG<br>4-6 mm <sup>2</sup>     | REFPO 5.5-120IN  | 13.0 | 18.0 | 28.0 | 37.0 | 13.0 | 6.7 | 3.4 | 1.0  |    |